



NOTE

1. ALL FENCE WOOD SHALL BE #1 CEDAR
2. ALL HARDWARE SHALL BE GALVANIZED OR NON-CORROSIVE
3. FACEBOARDS SHALL BE SCREWED TO CROSSBOARDS. ALL CROSSBOARDS WILL BE SCREWED TO POSTS (1 3/4" SCREWS). ALL CONCRETE FOOTINGS SHALL BE 6:1 BAC MAX, 2500 PSI CONCRETE

FENCE CLEAR SEALANT NOTE:

1. CONTRACTOR TO USE OLYMPIC WOOD PROTECTOR CLEAR WATER-PROOFING SEALER OR CONSTRUCTION MANAGER APPROVED EQUAL OLYMPIC PRODUCT. MAY BE PURCHASED AT LOCAL HARDWARE STORE
2. CONTRACTOR SHALL APPLY 2:1 TW GOALS OF ABOVE REFERENCE SEALER TO FENCE

ASSOCIATED ENGINEERING, INC
 211 N. MAIN STREET
 CHANDLER, AZ 85226
 P: 480-948-1111
 FAX: 480-948-1112
 AZ REG. PROJECT # 44

REGISTERED PROFESSIONAL ENGINEER
 REG. NO. 6498
 TOM MEDHI
 AZS1515251

PROJECT MANAGER

i wireless

APPLICANT/OWNER

SWS, LLC

DATE: THU THU

SITE NAME

ST. ISAAC

WIRELESS SITE NUMBER

SD0144

SUBMITALS

3	08/27/09	OWNER	OK
6	08/27/09	LAND	OK
6	08/27/09	ENV	OK
10	08/27/09	CON	OK

DRAWING TITLE

FENCE DETAILS

DRAWING NUMBER

C-5

SHEET NUMBER