

**INDEX OF SHEETS**

- C-101 SITE LAYOUT & UTILITY PLAN
- C-102 SITE GRADING & EROSION CONTROL PLAN
- C-103 La VILLA VISTA PLACE PLAN/PROFILE WEST 1/2
- C-104 La VILLA VISTA PLACE PLAN/PROFILE EAST 1/2
- C-105 CIRCLE ROAD PLAN/PROFILE
- C-106 11TH STREET SANITARY SEWER PLAN/PROFILE
- C-107 WEST STORM SEWER PLAN/PROFILE
- C-108 MIDDLE STORM SEWER PLAN/PROFILE
- C-109 EAST STORM SEWER PLAN/PROFILE
- C-110 CATHODIC PROTECTION DETAILS
- C-111 SITE DETAILS
- C-112 SITE DETAILS
- C-113 SITE DETAILS
- C-114 RETAINING WALL DETAILS

**Stormwater Pollution Prevention Plan  
DRAINAGE & EROSION CONTROL NOTES**

All grading and erosion control shall be in accordance with the City of Rapid City "Standard Specifications for Public Works Construction", 2007 Edition.

The approach locations shown hereon shall serve as stabilized construction entrances and be maintained in accordance with the Standard Specifications.

All disturbed, unpaved areas shall be reseeded and maintained until vegetation is established.

All work shall be in conformance with the Stormwater Pollution Prevention Plan currently in place for this development.

Stormwater conveyance elements are in substantial conformance with the Morningside Drainage Basin Design Plan (Ferber Engineering Co. 1988) on file with the City of Rapid City.

**PAVING NOTES**

Standard curb/gutter and fillets are to be constructed in accordance with the City of Rapid City "Standard Specifications for Public Works Construction", 2007 Edition.

**GENERAL NOTES**

All work shall be in accordance with the City of Rapid City "Standard Specifications for Public Works Construction", 2007 Edition.

Contractor shall be responsible of all permit acquisition and permit compliance.

Contractor shall prepare and submit a traffic control plan prior to commencement of work within the right-of-way.

All signage and traffic control measures within the right-of-way shall be in conformance with the "Manual on Uniform Traffic Control Devices", current edition.

**WATER MAIN NOTES**

All work shall be in accordance with the City of Rapid City "Standard Specifications for Public Works Construction", 2007 Edition.

Do not exceed pipe manufacturer's recommended allowances for vertical deflection. If pipe deflection exceeds manufacturer's recommended limit, use deflection couplings.

**FIRE HYDRANT TABLE**

STATION	OFFSET	BURY LINE ELEV.	APPROX INV.	LEAD LENGTH
0+87.13-16.95'	R	3248.96		5.5'
5+48.36-14.96'	L	3251.19		5.5'
8+39.34-24.84'	L	3246.40		5.5'

**PARKING SUMMARY**  
 GENERAL ONE PER COMPLETION UNIT X 48 UNITS = 48 SPACES  
 PROVIDE

