

## BRACING NOTES (NEW CONSTRUCTION) (CONTINUOUS STRUCTURAL PANEL)

1. ALL EXTERIOR WALLS SHALL BE SHEATHED WITH CONTINUOUS MIN. 7/16 STRUCTURAL WALL PANEL (OSB) IN ACCORDANCE WITH IRC SECTION R602.10.5

2. ALL INTERIOR WALLS SHALL BE CONSTRUCTED OF CONTINUOUS MIN. 1/2" GYP BD INSTALLED IN ACCORDANCE WITH IRC SECTION R602.10.5

3. THE FOLLOWING METHODS MAY BE USED ALTERNATE TO CONTINUOUS STRUCTURAL PANEL IN ACCORDANCE WITH IRC R602.10.6 THRU 10.9

(A) - METHOD 602.10.6-1 - 2'-8" TO 4'-0" LENGTH

(E) - SHEARWALL ANCHOR - 1'-4" TO 2'-8" LENGTH

## **GENERAL NOTES**

1. ALL INTERIOR DIMENSIONS ARE GIVEN FROM FACE OF STUD TO FACE OF STUD, OR FROM FACE OF STUD TO FACE OF CONCRETE, OR FACE OF CONCRETE TO FACE OF CONCRETE

2. ALL WINDOW & EXTERIOR DOOR DIMENSIONS ARE GIVEN AS APPROX, ROUGH OPENINGS.

3. ALL EXTERIOR WINDOW SIZES SHOWN ARE ROUGH OPENING SIZES, ALL DOOR SIZES SHOWN ARE UNIT OPENING SIZES,

4. ALL INTERIOR PARTITIONS ARE 2X4 WOOD STUD @ 16" O.C. UNLESS NOTED OTHERWISE, ALL EXTERIOR WALLS ARE 2X4 STUD @ 16" O.C. UNLESS NOTED OTHERWISE,