Low Maintenance & Easy Installation

Bellaforté Shake polymer roofing tiles make installation easy—saving materials and cutting down on installation costs. With little to no upkeep and backed by DaVinci's 50-year warranty, Bellaforté Shake tiles are the perfect fit for your home for generations to come.

A Safer & More Secure Roof

Bellaforté Shake has achieved the highest possible test ratings for fire, wind and impact giving you a more secure home for your family and has been approved and preferred by cities and subdivisions nationwide.

									New York Con-		
SPECIFICATION CHART											
Shingle Dimensions											
Widths			12" Thickness at			Butt	1" ave	1" average			
Length			15 1/2"-16" Thick			ickness at Tip			3/8"		
HIP - RIDGE - STARTER											
		0	One-Piece H		& Ridge	Rake	S	Starter		Transition Piece	
Pieces/Bundle			10			20	20	20		10	
Lineal Ft/Bundle)		20	20 20		10			
Pieces/Lineal Ft						1	1		1		
FIELD SHINGLES PER ROOFING SQUARE											
Coursing	Roof Pitch	Max. I	Exposure	T	Bundles/Square		Shingles/Squ		are	Weight/Square	
Straight	traight 4:12 or greater 12		2"		10		100	100		190 lbs	
PACKING AND SHIPPING INFORMATION											
			# Shingles				Weight				
Per Bundle *			10				19 lbs				
Per Pallet **			720				1,368 lbs				
Per Truckload ***			17,280				32,624 lbs				
* All weights are approximate ** 72 bundles per pallet *** 24 pallets per truckload											
TESTING SUMMARY											
Type of Test			Standard				Results				
Fire Test			ASTM E 108				Class A				
Impact Test			UL 2218				Class 4				
Wind Test			ASTM D 3161				Certified to 110 MPH				
Building Code Approvals: ICC-ES ESR 2119, Miami-Dade County, FL NOA No. 12-0831.01 and TDI											

^{*} Go to www.bellafortebydavinci.com for the most up-to-date technical information.

Toll Free: 800-DaVinci (328-4624) Phone: 913-599-0766 Fax: 913-599-0065 bellafortebydavinci.com davinciroofscapes.com