

RXV™



The E-Z-GO® RXV™ is the premier choice for any course, providing the highest level of durability, reliability and performance. Whether it's the electric model with an innovative AC Drive and full-time regenerative braking, or the gas-powered model with its best-in-class 13 hp Kawasaki engine, the RXV provides a superior golf experience and the greatest opportunity for lasting operational savings.

EXCELLENCE IN MOTION

**EZ-GO**


A Textron Company

**GAS**

BODY & CHASSIS	
Frame	Welded steel with DuraShield™ epoxy coating
Body & Finish	Molded-in color
Standard Color	Forest Green
DIMENSIONS	
Overall Length	94.5 in (240 cm)
Overall Width	47 in (119 cm)
Overall Height (no canopy)	45.7 in (116 cm) (top of steering wheel)
Overall Height (with canopy)	68.5 in (174 cm) (top of sun canopy)
Wheel Base	65.7 in (167 cm)
Front Wheel Track	35.5 in (90 cm)
Rear Wheel Track	38 in (97 cm)
Ground Clearance (at differential)	3.3 in (8 cm)
POWER	
Power Source	4-cycle 24.5 cu in (401 cc) low emissions
Valve Train	Single cylinder OHV
Horsepower (kW)	13 hp (9.7 kW) exceeds SAE J1940 standard
Electric System	Starter/generator, solid state regulator
Batteries (qty/type)	One, 12-volt maintenance-free
Air Cleaner	Remote intake, industrial-rated dry filter
Lubrication	Pressurized oil system
Oil Filter	Spin on
Cooling System	Air-Cooled
Fuel Capacity	6.2 gallon (23.5 L)
Drive Train	Automatic, continuously variable transmission (CVT)
Transaxle	Differential w/helical gears
Gear Selection	Forward-reverse
Rear Axle Ratio	11:42:1 (forward) 15:78:1 (reverse)
PERFORMANCE	
Seating Capacity	2-person
Dry Weight (without batteries)	697 lb (316 kg)
Curb Weight	747 lb (339 kg)
Vehicle Load Capacity	800 lb (360 kg)

PERFORMANCE CONT.	
Outside Clearance Circle	19 ft (5.8 m)
Forward Ground Speed	16.8 mph ± 0.5 mph
Reverse Ground Speed	12 mph ± 0.5 mph
Towing Capacity	3 golf cars with approved permanent tow bar
STEERING & SUSPENSION	
Steering	Double-ended rack and pinion
Front Suspension	Independent A-arm coilover spring shock
Rear Suspension	Mono-leaf spring w/hydraulic shocks
Service Brake	Rear wheel mechanical, self-adjusting drums
Parking Brake	Self-compensating, single point engagement
Front Tires	Turf 18 x 8.50-8 (4-ply rated)
Rear Tires	Turf 18 x 8.50-8 (4-ply rated)
OTHER STANDARD FEATURES	
Front and Rear Energy Transfer Bumpers, Sweater Basket with Individual Sections, Ergonomically Designed Console with Four Cup Holders and Integrated Ball and Tee Holders	

To learn more about the RXV™ or to receive a custom quote from your local E-Z-GO dealer, call: (800) 241-5855 or visit [www.ezgo.com](http://www.ezgo.com) today.



FRONT

ELECTRIC

BODY & CHASSIS	
Frame	Welded steel with DuraShield™ epoxy coating
Body & Finish	Molded-in color
Standard Color	Forest Green
DIMENSIONS	
Overall Length	94.5 in (240 cm)
Overall Width	47 in (119 cm)
Overall Height (no canopy)	45.7 in (116 cm) (top of steering wheel)
Overall Height (with canopy)	68.5 in (174 cm) (top of sun canopy)
Wheel Base	65.7 in (167 cm)
Front Wheel Track	35.5 in (90 cm)
Rear Wheel Track	38 in (97 cm)
Ground Clearance (at differential)	4.5 in (11 cm)
POWER	
Power Source	48-volt DC
Motor Type	48-volt AC
Horsepower (kW)	3 hp (2.2 kW) continuous
Electric System	48-volt
Batteries (qty/type)	Four, 12-volt deep cycle
Battery Charger	48 V Delta-Q high frequency, UL and CSA
Speed Controller	230-amp AC controller
Drive Train	Motor shaft direct drive
Transaxle	Limited slip differential
Gear Selection	Dash-mounted forward-neutral-reverse
Rear Axle Ratio	16:99:1
PERFORMANCE	
Seating Capacity	2-person
Dry Weight (without batteries)	571 lb (259 kg)
Curb Weight	919 lb (417 kg)
Vehicle Load Capacity	800 lb (360 kg)

PERFORMANCE CONT.	
Outside Clearance Circle	19.2 ft (5.8 m)
Ground Speed (level ground)	8-14.5 mph (12.2-24.1 kph) programmable
Towing Capacity	3 golf cars with approved permanent tow bar
STEERING & SUSPENSION	
Steering	Double-ended rack and pinion
Front Suspension	Independent A-arm coilover spring shock
Rear Suspension	Mono-leaf spring w/hydraulic shocks
Service Brake	Electric motor
Parking Brake	Automatic electro-magnetic
Front Tires	Turf 18 x 8.50-8 (4-ply rated)
Rear Tires	Turf 18 x 8.50-8 (4-ply rated)
OTHER STANDARD FEATURES	
Front and Rear Energy Transfer Bumpers, Sweater Basket with Individual Sections, Ergonomically Designed Console with Four Cup Holders and Integrated Ball and Tee Holders	



FRONT



SIDE



BACK

## RXV™ OPTIONS & ACCESSORIES

APPEARANCE	
Vehicle Color	<ul style="list-style-type: none"> <li>• Forest Green • Black • Flame Red • Ivory</li> <li>• Molten Red • Patriot Blue • Steel Blue • White</li> <li>(custom colors available)</li> </ul>
Seat Color	<ul style="list-style-type: none"> <li>• Stone Beige</li> </ul>
Weather Protection	<ul style="list-style-type: none"> <li>• Bag Cover: Tan, Oyster</li> <li>• Sun Canopy: Tan, Oyster</li> <li>• Fold Down Windshield</li> </ul>
ELECTRICAL	
Battery Charger (electric only)	<ul style="list-style-type: none"> <li>• 48 V Delta-Q w/18 foot DC Cord</li> </ul>
Other Electrical	<ul style="list-style-type: none"> <li>• Heavy-Duty Batteries (Trojan T-1275) (electric only)</li> <li>• Hour Meter (gas only)</li> <li>• Battery Fill System</li> <li>• Battery Fill System Nozzle</li> </ul>
TIRES AND WHEELS	
Tires	<ul style="list-style-type: none"> <li>• Links Turf 18 x 8.50-8 (4-ply rated)</li> <li>• T-Shot Turf 18 x 8.50-8 (4-ply rated)</li> </ul>
Wheel Covers	<ul style="list-style-type: none"> <li>• Platinum Spoke</li> </ul>
PERFORMANCE	
Divot Repair	<ul style="list-style-type: none"> <li>• Sand Bottle</li> <li>• Sand Bucket (driver, passenger)</li> </ul>
Other Options	<ul style="list-style-type: none"> <li>• Ash Tray</li> <li>• Club and Ball Washer (driver, passenger)</li> <li>• Cooler and Bracket (driver, passenger)</li> <li>• Insert</li> <li>• Message Holder • Fender Scuff Guard</li> <li>• SoftSwipe® Cleft Cleaner</li> <li>• Side Basket (driver, passenger)</li> <li>• Permanent Tow Bar</li> <li>• Handheld Diagnostic Tool</li> </ul>



COOLER



SAND BUCKET



BAG COVER

1451 Marvin Griffin Road, Augusta, GA 30906 | (706) 796-4311  
 Fax (706) 796-4540 | (800) 241-5855 | www.ezgo.com  
 e-mail: ezgo@textron.com | ©2007 E-Z-GO Division of Textron Inc.



822013-G1



A Textron Company