



OUTDOOR DISPLAY FEATURE INSTALLATION GUIDELINES

- VERIFY WITH THE STORE MANAGER THAT ALL RACKS ARE PROPERLY BUILT AND POSITIONED TO BE USED FOR ANCHOR. NOTE: BEHIND THE HOLE IN THE FRONT OF THE RACK IS A 2 1/2" DIA. ANCHOR. THE HOLE MUST BE FULLY THE GENERAL CONTRACTOR TO OBTAIN THE RACK SIZE AND TYP IN THE FIELD.
- ALL RACKS TO BE REINFORCED DOWN.
- SWEEP UP DRILLINGS AND ANY OTHER DEBRIS.

WAREHOUSE FEATURE INSTALLATION GUIDELINES

- CONCRETE IS TO VERIFY WITH THE STORE MANAGER THAT ALL RACKS ARE PROPERLY BUILT AND POSITIONED.
- SHALL BE USED FOR ANCHORING RACKS. GENERALLY THE HOLE IN THE FRONT OF THE RACK IS 2 1/2" DIA. ANCHOR. HOWEVER, THE HOLE MUST BE FULLY THE GENERAL CONTRACTOR TO OBTAIN THE RACK SIZE AND TYP IN THE FIELD.
- ALL RACKS TO BE SECURELY ANCHORED. FOLLOWING INSTALLATION, CLEAN AND REPAIR WALL, DOORS AND CLEAN AREA.

CASING SPECIFICATIONS

- FABRIC 30" x 60" GALV. (MINIMUM) OF 16GA CHAIN LINK FABRIC.
- TOP IN BOTTOM RAIL 1 1/2" DIA. FULL ROUNDED PIPES 2 1/2" DIA. FOR FOOT BRIMS. TOP RAIL TO BE JOINED W/ 1/2" SLEEVE. BOTTOM RAIL 8" DIA. ANCHOR.
- LINE POSTS 2 1/2" O.D. FULL WOOD PIPE, 3.5 LB. PER FOOT (MILL. LK. POSTS TO BE 3/4" DIA. 12'-0" ON CENTER WALL SPACING. SET IN 8" DIA. BY 20" DEEP CONC. FOOTING.
- TERMINAL POSTS 3" O.D. FULL WOOD PIPE, 3.75 LB. PER FOOT (MILL. LK. SET IN 8" DIA. BY 20" DEEP CONC. FOOTING.
- GATE POSTS 4" O.D. FULL WOOD PIPE, 8.10 LB. PER FOOT (MILL. LK. SET IN 8" DIA. BY 20" DEEP CONC. FOOTING.
- GATES TO BE 10'-0" x 6'-0" GALV. COATED CHAIN LINK GATE. 1/2" x 6" GALV. COATED CHAIN LINK GATES AND 1/2" x 6" BRASS GATE W/ FRANCHISE OF 1/2" FULL WOOD PIPE, 3.5 LB. PER FOOT (MILL. LK. SET IN 8" DIA. BY 20" DEEP CONC. FOOTING).
- ROLLING GATE DESIGN AS FOR THE MANUFACTURER DESIGN DRAWINGS. GATES SHALL BE MANUALLY OPERATED ROLLING CATERINGED BY RUBBER WHEELS AT FRONT OF GATE AND ISLAND STOPS AT GATE ENDS. ROLLERS TO BE 1/2" DIA. CON. SPRING GALVANIZED TENSION WIRE ATTACHED TO BOTTOM OF FENCE FABRIC W/ 8" DIA. HOOK END RING STOPS AT 2" O.C.
- INSTALL HEAVY BRACKET BAND AND CORNER BOLT PRESSURE STEEL FRAM. (END PRESSURE STEEL). LOCK UP PRESSURE STEEL CAN 12" x 24" TENSION BAR, HEAVY TENSION BAND AND CORNER BOLT.
- THE WIRE 80% 12 GA. STEEL TIE WIRE AND 80% 12 GA. STEEL WIRE SPACED 12" O.C. FOR LINE POSTS AND 24" O.C. HOOK END RING STOPS AT 2" O.C.
- POST FOOTING: TRUCK POURED CONCRETE.

UPPER DECK ARCHITECTS, INC.
 1301 W. GUNNABA ST., SUITE 212
 RAPID CITY, SD 57702
 PHONE 605.372.0327
 FAX 605.372.1524

DATE	DESCRIPTION	BY	CHKD.
07/27/20	ISSUED FOR PERMITS		

TRACTOR SUPPLY COMPANY
 Rapid City, South Dakota

TSC

PROJECT NUMBER: 08PD043
 DRAWN BY: [Name]
 CHECKED BY: [Name]
 SHEET TITLE: FLOOR PLAN