

**TORO**

# Groundsmaster® 4000-D/4010-D

WIDE AREA ROTARY MOWERS

## FEATURES

- 55 hp (41 kW) Yanmar® engine, Tier 4 Final Compliant, turbo-diesel engine
- Smart Power™ - optimized mowing in all conditions
- Foldable ROPS
- 11' (3.4 m) width of cut
- Full-time 4WD forward and reverse
- All-time traction assist assures full-time 4WD
- 0° uncut circle in turns
- SmartCool™ auto-reversing cooling fan
- HybridDrive™ cutting deck system delivers unmatched reliability
- 4-way adjustable seat and Air Ride Suspension
- InfoCenter™ displays simple operating info while monitoring machine health
- Integrated ControlHub™ with fingertip electronic controls
- Top and rear air intake for increased cooling
- Climate-controlled safety cab with air conditioning and heater (4010-D)
- Isolated operator platform for greater comfort and smoother ride

## Operator-friendly and smart by design.

With Smart Power™ technology, high engine torque and patented, HybridDrive™ cutting deck system, the Groundsmaster 4000-D and 4010-D deliver power where you need it most – to cut grass, no matter how tough the conditions. With their excellent trimming capability, you'll maneuver around obstacles with ease. Both mowers can mow a 0° uncut circle, allowing you to mow back and forth patterns without leaving any uncut grass. The patented, parallel hydraulic traction system maintains consistent hydraulic flow between the front and rear wheels to assure full time 4-wheel drive. This allows you to mow with confidence, even on hills and wet grass.

[toro.com/4000](http://toro.com/4000)



Groundsmaster® 4010-D

Groundsmaster® 4000-D

**4  
TIER****SMART POWER**

©2015 The Toro Company. All rights reserved. Rev. 8.15

Call your Toro distributor at 800-803-8676



# Groundsmaster® 4000-D/4010-D Specifications




GROUNDMASTER 4000-D, TIER 4 DIESEL, MODEL 30639 GROUNDMASTER 4010-D, TIER 4 DIESEL, MODEL 30636, Model 30607																
<b>ENGINE</b>	Yanmar® 4-cylinder, liquid-cooled, turbo-charged diesel. 127 cu. in. (2.1 liter) displacement. Engine rated at 55 hp (41 kW) net and 125 ft.-lbs. (169 Nm) torque at 2,000 rpm. 8 quart (7.6 liter) oil capacity. EPA Tier IV Final Compliant															
<b>AIR CLEANER</b>	Dry, replaceable primary and safety elements.															
<b>RADIATOR</b>	Rear-mount, cross-flow, 7-row, 6.3 fins per inch, 9 quart (8.5 liter) capacity.															
<b>FUEL CAPACITY</b>	21 gallons (79.5 liters) diesel fuel. Biodiesel-Ready for use up to B-20(20% biodiesel and 80% petroleum blend)															
<b>TRACTION DRIVE</b>	Parallel hydrostatic, closed loop system with full-time 4WD. Forward/reverse in low (mow) and high (transport) range with full-time, automatic traction assist (forward only) standard on Groundsmaster 4000-D models. Variable displacement piston pump with electronic servo control powers dual speed displacement piston motor drive into double reduction planetary in front, and mechanical axle in rear. SmartPower™ feature controls traction speed to maintain optimal cutting blade speed.															
<b>HYDRAULICS/COOLING</b>	8.75 gallon (33.1 liter) capacity with 10 micron remote spin-on filter. 9 row, single pass cooler, 6.3 fins per inch, that fills out for cleaning. Variable speed radiator cooling fan with automatic (based on coolant and oil temps) and manual reversing capabilities.															
<b>DIAGNOSTICS</b>	Diagnostic pressure test ports: forward and reverse traction, left, center and right decks, reverse 4WD, lift, steering, charge and deck counterbalance circuits.															
<b>GROUND SPEED</b>	<b>Transport:</b> 0-16.2 mph (0-26.1 km/h) forward, 0-8.1 mph (0-13 km/h) reverse. <b>Mow:</b> 0-8.3 mph (0-13.4 km/h) forward, 0-4 mph (0-6.4 km/h) reverse.															
<b>TIRES</b>	Front: 26 x 12-12, 6-ply tubeless Multi-Trac. Rear: 20 x 10-10, 6-ply tubeless Multi-Trac.															
<b>MAIN FRAME</b>	All welded formed-steel frame with integral tie-down anchors.															
<b>BRAKES</b>	Mechanically actuated, internal wet disc brakes on input to each planetary drive. Individual foot-operated steering brake control of left and right wheel. Lock pedals together and latch to engage parking brake.															
<b>SEAT</b>	4-way adjustable, right armrest travels with seat and suspension.															
<b>STEERING</b>	Power steering with dedicated power source. Steering wheel tilts to desired operator position. Uncut circle: 0" diameter.															
<b>INSTRUMENTATION</b>	InfoCenter™: Onboard LCD display shows gauges, alerts/faults, service reminders, electrical system diagnostics. Indicates fuel level, coolant temp, intake temperature, low oil pressure, alternator, engine hours, engine rpm, hydraulic oil temperature, voltage															
<b>CONTROLS</b>	Tilt steering, ignition switch, throttle switch, foot-operated traction pedal, lockable individual brake pedals, parking brake lock, mow/transport speed selector switch, 3-two position switches for individual deck lift/lower, counterbalance adjustment, tow valves, cup holder, toolbox, radio holder, fan switch and 12-volt power outlet.															
<b>ELECTRICAL</b>	12-volt, 690 cold cranking amps battery, 80 amp alternator (4010-D). Overload protection with automotive type fuses.															
<b>INTERLOCKS</b>	Prevents engine from starting unless traction pedal is in neutral and deck is disengaged. If operator leaves seat while moving or deck is engaged, traction and / or deck stops, info center alarms and gives message. Mowing only permitted in low range. Traction not allowed if parking brake engaged and pedal moved out of neutral, info center alarms and gives message. Deck transport latches.															
<b>GROUND CLEARANCE</b>	6.5" (16.5 cm)															
<b>OVERALL DIMENSIONS</b>	<table border="1"> <thead> <tr> <th>Height</th> <th>Length</th> <th>Width</th> <th>Transport Width</th> <th>Wheelbase</th> </tr> </thead> <tbody> <tr> <td>85" (216 cm) w/ROPS up</td> <td>135" (343 cm)</td> <td>136" (346 cm)</td> <td>71" (180 cm)</td> <td>55.5" (140 cm)</td> </tr> <tr> <td>93.9" (237 cm) w/ cab</td> <td>w/decks down</td> <td>w/decks down</td> <td>@ 2" (5 cm) HOC</td> <td></td> </tr> </tbody> </table>	Height	Length	Width	Transport Width	Wheelbase	85" (216 cm) w/ROPS up	135" (343 cm)	136" (346 cm)	71" (180 cm)	55.5" (140 cm)	93.9" (237 cm) w/ cab	w/decks down	w/decks down	@ 2" (5 cm) HOC	
Height	Length	Width	Transport Width	Wheelbase												
85" (216 cm) w/ROPS up	135" (343 cm)	136" (346 cm)	71" (180 cm)	55.5" (140 cm)												
93.9" (237 cm) w/ cab	w/decks down	w/decks down	@ 2" (5 cm) HOC													
<b>WEIGHT</b>	4205 lbs. (1907 kg) w/ full fluids (GM4000). 4759 lbs. (2159 kg) w/ full fluids (GM4010).															
<b>SAFETY CAB (4010)</b>	<b>MODEL 30636:</b> ROPS certified cab with heat, AC and the following standard features: climate system pressurized cab, heavy-duty pantograph front windshield wiper and washer, front windshield has 38" of visibility, interior mirror, fold away exterior side mirrors, molded front fenders, right and left doors and rear window have tinted (50%) glass, front and rear windows open, quick release window latches act as emergency exit, rubber sound isolator cab mounts and upholstered interior panels and headliner, textured neoprene floor mat, interior dome light. <b>MODEL 30607:</b> Factory installed, ROPS certified, climate controls (AC & heating), opening rear window, front wiper/washer, interior mirror, exterior side mirrors.															
<b>SAFETY</b>	Complies with American National Standards Institute (ANSI B71.4-2012) and applicable ISO EN 5395 (CE) (machine directive 89/392, 91/368, 93/44, 84/538, 89/336) requirements; Optional lights. Meets ANSI/ASAE 5279.12 (Lighting and Marking of Agricultural Equipment on Highways). Foldable ROPS, ISO 21299 certified.															
<b>WARRANTY</b>	Two-year limited warranty. Refer to operator's manual for further details.															
<b>ACCESSORIES</b>	Work light, Road lights consisting of dual taillights, dual headlights, slow moving vehicle sign, turn signal, flasher and lights; Sunshade Beacon															
<b>CUTTING DECKS</b>																
<b>WIDTH OF CUT</b>	Overall: 132" (335 cm), Front: 62" (157.5 cm), Wings: 42" (106.7 cm), Overlap: 7" (12.8 cm).															
<b>MOWING RATE</b>	Mows up to 11.0 acres/h (4.5 hectares/h) at 8.5 mph (13.4 km/h) (assumes no overlap or stops).															
<b>CONSTRUCTION</b>	Welded .100" (25 mm) steel with 7 and 10-gauge steel channel and plate reinforcements, buttnose bumpers.															
<b>DECK DRIVE</b>	Direct mounted hydraulic motor into spindle. Remaining spindle(s) driven by individual B section kevlar belt. Quick release belt covers.															
<b>HEIGHT-OF-CUT</b>	1"-5" (25-127 mm) in .5" (13 mm) increments.															
<b>SPINDLES</b>	1.25" (3.17 cm) diameter spindle shafts, 9" (22.9 cm) diameter conical ductile iron housing, and 2 greaseable tapered roller bearings.															
<b>BLADES</b>	21.75" (55.2 cm) long, 2.5" (6.4 cm) wide, .25" (.64 cm) thick.															
<b>CASTER WHEELS</b>	8 x 3.50-4, 4-ply, smooth, pneumatic, sealed precision ball bearings.															
<b>GROUND FOLLOWING</b>	6" anti-scalp cups on each blade, adjustable skids on each deck, 4 anti-scalp rollers on front deck and 1 on each wing.															
<b>WING PROTECTION</b>	Bi-directional, impact absorption device on each wing deck.															
<b>RECYCLER KIT</b>	Model 30420 will convert decks into Guardian® Recycler® decks.															
<b>MULCHING KIT</b>	Model 30422.															
<b>SKIDS</b>	Reversible polymeric.															

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.





# Groundsmaster® 4000-D Attachment Specifications



ROTARY BROOM, MB MODEL HCT**	
<b>TYPE</b>	Windrow type, front mounted hydraulic broom with dual motors. Electric/hydraulic angling, 30° left and right.
<b>BROOM SIZE</b>	32" (81 cm) diameter x 60" (153 cm) wide.
<b>BRUSH</b>	Sectional brush with combination polypropylene/wire radial segments.
<b>WEIGHT</b>	460 lbs. (209 kg)
<b>OPTIONS</b>	Dirt Deflector, Storage Stands.



SUNSHADE	
<b>UNIVERSAL MOUNT SUNSHADE</b>	White, Model 30349
<b>UNIVERSAL MOUNT SUNSHADE</b>	Red, Model 30552



SNOWTHROWER ERSKINE MODEL 2000***	
<b>STAGE</b>	2
<b>WIDTH OF CUT</b>	61" (155 cm)
<b>CUTTING HEIGHT</b>	29" (74 cm)
<b>CUTTING EDGE</b>	3/8" x 3" (9.5 mm x 7.6 cm) bolt-on
<b>SKID SHOES</b>	Adjustable
<b>AUGER DIAMETER</b>	16" (41 cm) open flight
<b>FAN DIAMETER</b>	20" (51 cm) 4-blade
<b>CHUTE ROTATION</b>	Hydraulic 270°
<b>SHEAR PROTECTION</b>	Pressure relief
<b>CASTING DISTANCE</b>	Up to 30' (9.14 m)
<b>APPROXIMATE SHIPPING WEIGHT</b>	850 lbs. (386 kg)
<b>HOSES</b>	Included

\*Specifications and design subject to change without notice.

\*\* Manufactured by M-B Companies Inc.

\*\*\* Manufactured by Erskine Attachments.

Note: The Toro Company does not manufacture or sell the snowthrower or rotary broom, nor does Toro guarantee these accessories in any manner whatsoever.

